



## SHRINK BAGS & FILM

### THE BASICS

Our Shrink Bags are designed to protect pallets and secure loads during transportation. Once the bag is placed over the product, heat is then applied to the film. This results in a glove like cover that prevents the contents from shifting or moving out of place.

Shrink Bags are often used in place of stretch film, here's why:

- ▶ They provide stronger containment for pallets and loads that are heavier, irregularly shaped or will be in outside storage.
- ▶ They serve as a quicker alternative in the palletization process, as they are entirely in one piece.

Shrink Bags may be used to cover pallets containing the following products:

- ▶ Corrugated gaylords
- ▶ Furniture
- ▶ Bricks and blocks
- ▶ Bags of aggregate
- ▶ Sand
- ▶ Other irregularly shaped objects

#### TECHNICAL DETAILS

Made from a blend of Low-Density Polyethylene with a High Slip additive. These can be shrunk using a heat gun or integral heat tunnel and provide a secure glove-like cover after heat is applied. All bags are available on rolls with 3" cores and open from the side.



### SHRINK BAGS ON ROLLS

Made from a blend of Low-Density Polyethylene with a High Slip additive. These can be shrunk using a heat gun or integral heat tunnel and provide a secure glove-like cover after heat is applied. All bags are available on rolls with 3" cores and open from the side.

#### 4 MIL STOCK PALLET-SIZE SHRINK BAGS

ITEM	W x D x L	CNT	WT
13500	44 X 44 X 70	25	40
13510	48 X 46 X 72	25	43
13520	50 X 44 X 57	25	34
13530	50 X 48 X 84	25	52
13540	52 X 43 X 70	25	42

**BUILD ANY SIZE: Mil: 1-8.5 (7.5 for gusseted)**  
**Width: 24"-125" Length: 24"-300"**  
**MORE OPTIONS: Materials, Film Color, Venting, Packaging Details**



### SHRINK BUNDLING FILM

Our Shrink Bundling Film is designed for use on automated packaging equipment with integral heat tunnels for a "bullseye" closure. This film ensures that heavier product is securely packaged and will not fall out of place.

#### TECHNICAL DETAILS

Made from a three-layer blend of Polyethylene and is engineered to provide superior clarity, tensile strength and puncture resistance. All film demonstrates a consistent shrink performance of 60-80% (MD) and 0-20% (TD). Packaged on rolls with 3" cores.

#### 2 MIL STOCK ITEMS

ITEM	WIDTH	FT/RL	WT
13550	16"	4200	54
13552	18"	4200	61
13554	20"	4200	67
13556	22"	4200	74
13558	24"	4200	80

CONTACT US FOR  
MORE INFORMATION



Veteran Packaging Company  
900 Rutter Avenue  
Forty Fort, Pennsylvania 18704

www.vetpackagingco.com  
bsmith@vetpackagingco.com

**410-830-9496**